



ENGINE OIL TLE

5W-30

Product Description:

ENGINE OIL TLE 5W-30 is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particle Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

ENGINE OIL TLE 5W-30 is formulated on high refined synthetic base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals up to 150.000 km.
- Suitable for engines equipped with a Diesel Particulate Filter (DPF).
- Fuel conserving.



ENGINE OIL TLE 5W-30 exceeds the following performance criteria.:

Approved: Volvo VDS 4.5 Mack EOS-4.5 Renault VI RLD-3
DTFR 15C110 (MB 228.51)

Exceeds: API CK-4 ACEA E7/E8/E11 API SN
CAT ECF-3 Scania LDF-4 MAN M3677
MAN M3777 MAN M3775 Cummins CES 20086
DDC 93K222 DAF IVECO
MTU 3.1 Deutz DQC IV-18-LA JASO DH-2

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	5W-30
Density@15°C	kg/m ³	ASTM D4052	852.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	72.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	167
Viscosity CCS @ -30°C	cP	ASTM D5293	5900
Total Base Number	mgKOH/g	ASTM D2896	9.6
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-33
Sulphated Ash	%Wt	ASTM D874	0.9

Product Nr: 42511

Date Superseded: -

Date Issued: 6-12-2024

Revision nr: -