

MOTOR OIL SYNTHETIC LE

5W-30

Product Description:

Motor Oil Synthetic LE 5W-30 is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger car and light vans with or without turbocharger.

Motor Oil Synthetic LE 5W-30 is developed for use in engine which are equipped with or without an exhaust gas after treatment system.

Motor Oil Synthetic LE 5W-30 is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.
- Excellent detergency and dispersency properties.

Motor Oil Synthetic LE 5W-30 exceeds the following performance criteria.:

Approved: MB-Approval 229.52 MB-Approval 229.51 BMW LL-04 (Pending)

(Pending) (Pending)

Exceeds: ACEA C3 API SP Renault RN17

MB 229.31 MB 226.52 DEXOS 2

OV 040 1547 – G30 OV 040 1547 – D30

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m3	ASTM D4052	853.4
Kin. Viscosity @40°C	mm2/s	ASTM D7042	68.8
Kin. Viscosity @100°C	mm2/s	ASTM D7042	11.8
Viscosity Index		ASTM D2270	170
Viscosity CCS	cР	ASTM D5293	6310
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.7
Sulphated Ash	%Wt	ASTM D874	0.8

Product Nr: 42255 **Date Issued:** 19-6-2025

Date Superseded: 27-11-2024 Revision nr: 03

