



MOTOR OIL XT 5W-30

Product Description:

MOTOR OIL XT 5W-30 is a high performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed. **MOTOR OIL XT 5W-30** is suitable for vehicles where MB 229.51 and BMW LL-04 are required.

Remark: not suitable for R5- and V10 TDI engines and engines where VAG norm VW 506.01 is being advised.

For vehicles within warranty or extended warranty we advise to use MOTOR OIL VX 0W-30 or MOTOR OIL VX 5W-30



MOTOR OIL XT 5W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

MOTOR OIL XT 5W-30 exceeds the following performance criteria:

ACEA C3

BMW LL-04 > until 2019

VW 504.00 / 507.00

API SP

MB 229.52

MB 229.51

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m ³	ASTM D4052	851.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	73.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	164
Viscosity CCS @-30°C, max	cP	ASTM D5293	6270
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.3
Sulphated Ash	%Wt	ASTM D874	0.79

Product Nr: 42310

Date Superseded: 28-11-2024

Date Issued: 9-5-2025

Revision nr: 09