



PSF SYNTH

Product Description:

PSF SYNTH is a fully synthetic power steering fluid dedicated for most common passenger cars and light-duty commercial vehicles.

PSF SYNTH is formulated from specially selected high quality fully synthetic Poly-alpha olefin (PAO) base stocks in combination with a special detergent additive to achieve the following performance:

- Excellent cleaning properties
- Improves performance and smoothness of operation in power steering systems
- High Viscosity Index
- Miscible with all common power steering fluids.
- Very bright and light colored oil helps improves visual detection when flushing is completed; reducing total volume of used flushing oil



PSF SYNTH is recommended where the following OEM specifications / part numbers are required:

Acura/Honda PN 08206-9002		American Motors Corporaton C4124	
Audi PN G002000	Bentley JNV862564F	Bosch ZF TE-ML 09	Chrysler MS-11655B
Chrysler MS-90030	DaimlerChrysler MS1872	DaimlerChrysler MS5931F&G	
DaimlerChrysler MS9602	DaimlerChrysler MS9933A	DaimlerChrysler MS1872	Fendt X 902 011 622
Ford M2C195A	Ford M2C33F	Ford ESW-M2C128 C&D	Ford M2C128D
Ford MS2195A	Ford M2C138C	Ford M2C138CJ	Ford WSS M2C204A
GM 9985010	GM 9985835	GM 89021184	Honda
Hyundai/Kia PSF-3	Hyundai 00232-19017	Iveco 18-1823	Land Rover LR003401
MAN M3289	MAN Type L1/L2	Massey Ferguson	MB 345.0
Mitsubishi PS Fluid/Diamond SP III		Navistar TMS 6810	NH 610A
Nissan PSF-II	Opel B 040 0070	Opel B 040 2012	Pentosin CHF 11 S
Pentosin CHF 202	Porsche 000 043 206 56	Porsche 000 043 203 33	PSA B71 2710
PSA S71 2710	Saab 93160548	Saab 3032 380	Saab PSF 2634
Saab PSF 45 30 09 800	Saab PSF 93160548	Saab PN 30 09 800	SDFG OF1611S
Subaru PN K0209A0080	VW G 004 012	Volkswagen VW-TL-570-26	Volkswagen VW-TL-52 146.01
Volvo 1161529	Volvo 30741424		

PSF SYNTH is suitable for use where these specifications are required for power steering fluid. It is not suitable in other applications such as automatic transmissions.

Property	Unit	Test Method	Typical Value
Color			Green
Density@15°C	kg/m ³	ASTM D4052	827.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	19.0
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.7
Viscosity Index		ASTM D2270	323
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-60

Product Nr: 43190

Date Superseded: 14-01-2025

Date Issued: 23-10-2025

Revision nr: 08