



ATF

MV

Product Description:

ATF MV is a high quality synthetic fluid specially designed with advanced multi-vehicle additive technology to serve a broad range of. ATF MV exceeds the complex requirements of Automatic Transmission/ Vehicle Manufacturers of Europe, North America and Asia including the JASO 1-A performance standard created by Japanese Automobile Manufacturers Association.

Remark: Not suitable for use in Continuously Variable Transmissions (CVT), Dual Clutch Transmission (DCT), Daimler MB 7 speed (NAG 2), ZF 6 Speed.

ATF MV is based on fully synthetic base in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Excellent lubrication, even under extreme conditions.
- Very high protection against wear, corrosion and foam.
- High “shear stable”.
- Very low Pour point, can be used by very cold temperatures.
- High Viscosity Index.

ATF MV exceeds the following performance criteria:

Allison C4, TES 295	LT 71141, LA 2634	ETL -7045E, 8072B	Chrysler AS68RC
ATF Chrysler +3, +4	Ford Mercon	Ford Mercon V	Dexron IID, IIIG/H
Honda Z1	Mitsubishi SP-II / III	Hyundai/ KIA SPII /III	Idemitsu K17 / ATF HP
JWS 3309/3314/3317	JASO M315-2004	Texaco N402	MAN 339 V1/Z1/Z2
Mazda ATF M-III, M5	MB 236.3, 5, 6, 7, 8	MB 236.9, 10, 11, 91	Nissan Matic D,J,K,W
Subaru ATF, HP	Toyota T-III, T-IV	Voith H55.6335.xx	Volvo Std 1273.4
VW G 052 025	VW G 055 025	VW G 052 162	VW G 052 990
Volvo P/N 1161521	Volvo 1161540	Volvo 1161640	Volvo CE 1273,41
PSA P/N Z 000169756	Ssang Yong DSIH 5M-66	ZF TE ML 03D, 04D, 11A/B, 14A/B, 16L/R, 17C, 20B, 25B	



Property	Unit	Test Method	Typical Value
Color		Visual	Colorless to light Yellow
Density @15°C	kg/m ³	ASTM D4052	846.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	35.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.6
Viscosity Index		ASTM D2270	188
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51

Product Nr: 43230

Date Superseded: 13-12-2019

Date Issued: 30-12-2024

Revision nr: 06