



LHM FLUID

Product Description:

LHM FLUID is a high performance hydraulic oil , especially developed for the hydraulic brake-power steering- and suspension systems of Citroën and certain other vehicles.

LHM FLUID complies with the latest demands of Citroën. **LHM FLUID** has been fortified with additives to withstand oxidation at the high temperatures encountered in the disc braking systems and to protect the system against rust and corrosion. **LHM FLUID** shows an extreme fluidity at low temperature, realizing immediate response of the systems under all climatically conditions.

LHM FLUID is a one of a kind hydraulic oil comprising of special base stocks and unique additives to obtain an exceptional high and stable Viscosity Index (VI), and a very low pour point.

WARNING:

LHM FLUID should never be used in brake systems other then those described above, where in a BRAKE FLUID DOT 3, 4, 5 or 5.1 is prescribed.

LHM FLUID exceeds the following performance criteria:

ISO 7308

PSA B71 2710 or PSA Company (Citroën, Peugeot)



Property	Unit	Test Method	Typical Value
Density@15°C	kg/m ³	ASTM D4052	840
Kin. Viscosity @-40°C	mm ² /s	ASTM D7042	1200
Kin. Viscosity @100°C	mm ² /s	ASTM D5293	6.15
Viscosity Index		ASTM D2270	320
Flash Point COC	°C	ASTM D92	125
Pour Point	°C	ASTM D97	-51

Product Nr: 43930

Date Issued: 08-08-2011

Date Superseded: 12-07-2010

Revision nr: 01