



# ANTIFREEZE

## Product Description:

**ANTIFREEZE** is a silicate, amine-, nitrites- and phosphates free antifreeze concentrate providing frost and corrosion protection. For the perfect operation of water-cooled internal combustion engines.

**ANTIFREEZE** may not be used undiluted in a combustion engine.

**ANTIFREEZE** is based Mono Ethylene Glycol in combination with a powerful additive technology to obtain the following benefits:

- Corrosion protection, also for non-ferro metals.
- Frost protection.
- Boiling protection.
- Seal compatibility.
- Hard water stability.
- Miscibility.

**ANTIFREEZE** meets the following performance criteria:

**British Standard (BS) 6580**  
**SAE J-1034**

**AFNOR 15-601**    **ASTM D3306**  
**CUNA NC 956-16**



Property	Unit	Test Method	Typical Value
Color			Blue
Density @15°C	kg/m <sup>3</sup>	ASTM D5931	1.131
Equilibrium Boiling Point	°C	ASTM D1120	155
Reserve Alkalinity (pH 5.5)		ASTM D1121	3.0
Refractive Index, 20°C		ASTM D1218	1.435
Freezing Protection			
33% dilution with water	°C		-17
50% dilution with water	°C		-33

**Product Nr:** 43940  
**Date Superseded:** 29-05-2018

**Date Issued:** 23-12-2019  
**Revision nr:** 03