



Gulf Formula GX 5W-40 Passenger Car Motor Oil

Product Description

Gulf Formula GX series are the most advanced high performance synthetic passenger car motor oils exclusively developed for latest generation passenger cars and light duty vehicles. The latest formulation technology used in this oil provides unmatched levels of overall lubrication for all types of vehicles, especially high output, turbocharged, supercharged multi valve fuel injected engines in passenger cars, SUVs, light vans & trucks. It is specially designed to ensure maximum protection over extended oil-change intervals. It exceeds the requirements of virtually all the major global OEMs and industry standards.

Features & Benefits

- Outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended drain intervals & engine life
- Superior antiwear technology provides exceptional wear protection under all conditions
- Excellent low volatility characteristics reduce oil consumption & hydro-carbon pollution
- Active cleaning agents ensure maximum engine cleanliness
- Enhanced frictional properties result in fuel savings
- Excellent low temperature properties lead to quick cold start and ensure wear protection at start-up

Applications

- Recommended for all latest, high performance gasoline and diesel engines in cars, SUVs, light vans & trucks, particularly those using recent technologies (multi-valve engines, turbo compressors, and high cylinder capacity) and the new direct injection diesel engines with or without common rail
- Especially suited to city stop-and-go, heavy load and/or high-speed applications where the conventional oils fail to perform and where such quality oils are recommended

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-40
ACEA A3/B4, RN 0700		X
BMW Longlife-01		X
Porsche A40		X
Renault RN0710		X
Recommendation		
Fiat 9.55535-Z2		X
Has the following Approvals		
API SN		X
MB-Approval 229.5, VW 502 00, 505 00		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	14.2
Viscosity Index	D 2270	168
Flash Point, °C	D 92	230
Pour Point, °C	D 97	-36
TBN, mg KOH/g	D 2896	10.5
Density @ 15°C, Kg/l	D 1298	0.85
Sulphated Ash, %wt	D 874	1.29

Gulf Europe - April 2023

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com