



Gulf Formula PCX

Catalyst Compatible Synthetic Passenger Car Motor Oil

Product Description

Gulf Formula PCX is an advanced high-performance passenger car motor oil formulated from synthetic base stocks and state-of-the-art additive technology to provide fuel savings apart from maintaining the efficiency and help extending the life of emission reduction systems. It is fully compatible with Diesel Particulate Filter (DPF) and Gasoline Three Way Catalyst (TWC). It is specially developed to exceed the service fill requirements of PSA Peugeot Citroën vehicles and vehicles of other make requiring ACEA C2 type of oils.

Features & Benefits

- Mid SAPS (**S**ulphated **A**sh **P**hosphorus **S**ulphur) oil formulation helps prolong the life and maintain the efficiency of DPF and TWC.
- Outstanding thermo-oxidative stability resists oil degradation and thus facilitates extended oil change intervals
- Active cleaning agents reduce deposits & sludge and keep engine clean.
- Enhanced frictional properties provide improved fuel economy (ACEA C2) compared to mineral engine oils.
- Excellent antiwear properties lead to superior wear protection
- Exceptional Stay-in-Grade performance ensures reliable lubrication even at higher loads & operating temperatures
- Outstanding low temperature fluidity aids quick cold start and provides wear protection at start-up

Applications

- Latest generation passenger cars, SUV's and light vans of Peugeot and Citroën requiring oils meeting the PSA Peugeot Citroën B71 2312 specification.
- Modern high-performance gasoline and diesel engines in passenger cars and light duty vehicles fitted with DPF and TWC requiring catalyst compatible fuel economy oils meeting ACEA C2 specifications.
- This oil may be unsuitable for use in some engines (consult owner's manual/ handbook).

Specifications, Approvals & Typical Properties

Meets the following Specifications		0W-30
ACEA C2, PSA B71 2312		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	9.7
Viscosity Index	D 2270	166
Flash Point, °C	D 92	205
Pour Point, °C	D 97	-42
Density @ 15°C, Kg/l	D 1298	0.853
Sulphated Ash, %wt	D 874	0.58
Phosphorus, %wt	D 4047/ICP	0.062

April 2023 - GOSCO

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com