



Gulf Formula RNX

Catalyst Compatible Passenger Car Motor Oil

Product Description

Gulf Formula RNX is synthetic, catalyst compatible passenger car motor oil specially designed using most modern additive chemistry meeting Low SAPS (Sulphated Ash, Phosphorous & Sulphur) requirements for vehicles meeting Euro IV norms. It has been exclusively developed for use in high performance gasoline and diesel engines requiring low SAPS oil with HTHS greater than 3.5mPa.s in passenger cars and light vans fitted with Diesel Particulate Filter (DPF) and Three Way Catalyst (TWC) to extend life and maintain efficiency of these after treatment devices. It provides exceptional wear protection and minimizes deposits in engine and turbocharger. It is developed to exceed the service fill requirements of most recent models of Renault and other OEMs requiring ACEA C4/C3 type of oils.

Features & Benefits

- Low ash content reduces particulate build-up in diesel particulate filters used in diesel cars
- Latest additive technology with active cleaning agents reduces piston deposits, sludge build-up and soot related oil thickening facilitating extended engine life
- Excellent thermo-oxidative stability reduces oil degradation and enables extended drain intervals
- Excellent antiwear technology leads to superior wear protection
- Low volatility ensures reduced oil consumption and emissions
- Excellent low temperature property aids cold start and protects against wear at start-up

Applications

- Recommended for latest Renault Cars in particular for Diesel cars with DPF and meeting Euro 4 emission norms requiring oils meeting Renault specification RN 0720
- Latest generation high performance gasoline and diesel engines in modern passenger cars light vans fitted with DPF and TWC requiring catalyst compatible oils meeting ACEA C4/C3 specifications
- These oils may be unsuitable for use in some engines requiring high viscosity grade oils or in markets where fuel sulphur content is high (consult owner manual/ handbook)

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-30
ACEA C4/C3		X
Renault RN 0720, MB 229.51, MB226.51		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	12.0
Viscosity Index	D 2270	165
Flash Point, °C	D 92	212
Pour Point, °C	D 97	-33
TBN, mg KOH/g	D 2896	6.2
Density @ 15°C, Kg/l	D 1298	0.842
Sulphated Ash, %wt	D 874	0.49
Phosphorus, %wt	D 4047/ICP	0.071
Sulphur, %wt	D 129	0.19

June, 2023

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com