



Gulf MAX Ultra Plus

Semi-Synthetic Passenger Car Motor Oil

Product Description

Gulf MAX Ultra Plus is a high performance semi-synthetic passenger car motor oil designed to provide optimum performance in high-output, multi valve, turbocharged & supercharged gasoline and diesel engines of passenger cars, vans, SUVs and light-duty trucks. Its specially chosen additive technology enables reliable performance across different operating conditions while meeting the requirements of leading passenger car manufacturers and global industry standards.

Features & Benefits

- Excellent thermo-oxidative stability helps minimise sludge build-up, reduces oil thickening to facilitate extended oil drain interval and ensure engine cleanliness
- Improved detergency protects against engine deposits to ensure reliable performance
- Excellent antiwear technology minimises engine wear to reduce maintenance costs
- Good low temperature fluidity coupled with viscosity retention at higher temperature offers reliable protection over a wide temperature range

Applications

- Suitable for North American, European & Japanese high output gasoline engines & diesel engines in passenger cars, SUVs, vans, and light-duty trucks where API SN, API SM, API SL and/or ACEA A3/B4 quality oils are specified.
- High performance, multi valve, turbocharged & supercharged engines of passenger cars, vans, SUVs & light-duty trucks operating under city stop-and-go, high-speed and/or high load conditions.

Note: Not suitable for vehicles meeting emission standards beyond Euro 4. For such applications requiring catalyst compatible oils, please contact your Gulf representative.

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-40
ACEA A3/B4		X
MB 226.5		X
VW 501 01 / 505 00		X
Renault RN0710/0700		X
Recommendation		
FIAT 9.55535-D2		
Has the Following Approvals		
API SN, MB-Approval 229.3		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	15.0
Viscosity Index	D 2270	153
Flash Point, °C	D 92	232
Pour Point, °C	D 97	-33
TBN, mg KOH/g	D 2896	10.4
Density @ 15°C, Kg/l	D 1298	0.873
Sulphated Ash, %wt	D 874	1.31

Gulf Europe, March 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com