



Gulf Superfleet Professional ECON

Advanced Full Synthetic Engine Oil for Heavy Duty Diesel Engines

Product Description

Gulf Superfleet Professional ECON 5W-30 is a synthetic ultra high performance diesel engine oil exclusively designed for new generation, high performance, low emission engines.. This oil is formulated using the most advanced additive technology and synthetic base fluids to provide potential fuel economy benefits, outstanding high temperature viscosity retention, low temperature fluidity, cleaner engines and volatility control. The latest low SAPS (Sulphated Ash, Phosphorus, Sulphur) additive chemistry used in this oil facilitates in maintaining the efficiency of the emission reduction systems such as Diesel Particulate Filter (DPF), which is used to meet Euro 6 emission requirements. This oil is also suitable for application in HD gas engines.

Features & Benefits

- The latest state of the art additive technology provides exceptional thermo-oxidative stability for protecting engine components against high temperature deposits, sludge build-up and oil thickening.
- The most advanced low SAPS additive technology protects after treatment devices from deposits and deterioration of catalysts.
- Superior shear stability reduces viscosity breakdown and oil consumption.
- Excellent low temperature fluidity enables easy pumpability and circulation at low ambient temperatures and provides wear protection at start-up.
- Excellent antiwear property and high temperature-high shear viscosity provide protection against engine wear & bore polishing facilitating extended engine life.

Applications

- Recommended for highly rated latest generation low emission vehicles meeting Euro 6, Euro 5 and earlier emission norms.
- Suitable for EGR engines with or without particulate filters and for engines fitted with SCR NOx reduction systems.
- Strongly recommended for engines fitted with particulate filters and is designed for vehicles running on low sulphur diesel fuel (Max. 50 ppm).
- Specially recommended for MAN trucks requiring MAN M 3677 quality oils.
- Suitable for application in HD gas engines

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-30
ACEA E6/E7/E8/E9/E11, DTFR 15C100 (MB 228.31), Cummins CES 20086, DDC 93K222		X
Scania LDF-4, Deutz DQC IV-18 LA, MTU Oil Category 3.1		X
JASO DH-2, MAN M3677/M3477/M3271-1/M3775, Ford WSS M2C213-A1		X
IVECO 18-1804 TLS E6, DAF Extended Drain, CAT ECF-3		X
Has the following Approvals		
API CK-4/SN, DTFR 15C110/15C120 (MB-Approval 228.51/228.52)		X
Volvo VDS-4.5/ Mack EO-S 4.5/ Renault VI RLD-3 approval		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	12.4
Viscosity Index	D 2270	163
Flash Point, °C	D 92	229
Pour Point, °C	D 97	-42
TBN, mg KOH/g	D 2896	10
Density @ 15°C, Kg/l	D 1298	0.85
Sulphated Ash, wt%	D 874	0.97
Phosphorus, wt%	D 4047 / ICP	0.078
Sulphur, wt%	D129 / ICP	0.20

Gulf Europe, Nov. 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com