Product Data Sheet

## MOTOR OIL VX **OW-20**

## **Product Description:**

**MOTOR OIL VX 0W-20** is a fully synthetic fuel saving long life oil based for use in gasolineand diesel engines of passenger cars and light vans where a VAG norm 508.00/509.00 has been prescribed.

## Remark: This product is not backwards compatible with older vehicles that require the VW 504 00/507 00 specification.

**MOTOR OIL VX 0W-20** is formulated with high quality 100% Poly Alpha Olefin (PAO) base stocks in combination with an unique additive technology to achieve the following performance:

- Exceptional good low temperature properties.
- Excellent protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Improved fuel economy.

MOTOR OIL VX 0W-20 exceeds the following performance criteria:

Exceeds	VW 508 00 / ACEA C5 Ford WSS-M		VW TL 52577 Porsche C20	
Property		Unit	Test Method	Typical Value
SAE Grade			SAE J300	0W-20
Density@15°C		kg/m <sup>3</sup>	ASTM D4052	846.4
Kin. Viscosity @40°C		mm²/s	ASTM D7042	44.1
Kin. Viscosity @100°C		mm²/s	ASTM D7042	8.3
Viscosity Index			ASTM D2270	167
Viscosity CCS @-35°C, max		сР	ASTM D5293	5560
Flash Point COC		°C	ASTM D92	>205
Pour Point		°C	ASTM D7346	-51
Total Base Number		mgKOH/g	ASTM D2896	8.9
Sulpated Ash		%Wt	ASTM D874	0.8

**Product Nr:** 42170 **Date Superseded:** 25-10-2024 Date Issued: 3-12-2024 Revision nr: 06

