

## MONO ENGINE OIL CF

## **10W**

## **Product Description:**

**MONO ENGINE OIL CF 10W** is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions.

**MONO ENGINE OIL CF 10W** is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended.

**MONO ENGINE OIL CF 10W** is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

**MONO ENGINE OIL CF 10W** exceeds the following performance criteria:

 API CF-4
 API SG
 ACEA E2
 Volvo VDS

 MB 228.0
 MB 228.1
 MAN 270
 MAN 271

 Deutz DQC I-02
 ZF TE-ML 04A
 ZF TE-ML 04P
 ZF TE-ML 07D

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	884.7
Kin. Viscosity @40°C	mm²/s	ASTM D7042	40
Kin. Viscosity @100°C	mm²/s	ASTM D7042	6.4
Viscosity Index		ASTM D2270	110
Viscosity CCS @-25°C	cР	ASTM D5293	6490
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	11.8

**Product Nr:** 42620 **Date Issued:** 4-4-2025

**Date Superseded:** 30-06-2023 **Revision nr:** 08

