



# AUTOGEAR OIL EP

## 80W-90

### Product Description:

**AUTOGEAR OIL EP 80W-90** is an universal high performance mineral EP gear oil for use in manual transmission and transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 80W-90 GL-4 is been required.

**AUTOGEAR OIL EP 80W-90** is formulated with high refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Good Extreme Pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR OIL EP 80W-90** exceeds the following performance criteria:

**API GL-4    MIL-L-2105    BW-TL 9150-0010**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	80W-90
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	880.4
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	127.7
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	14.4
Low-Temperature Brookfield Viscosity @ -26°	cP	ASTM D2983	61000
Viscosity Index		ASTM D2270	113
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33

**Product Nr:** 43020  
**Date Superseded:** 24-6-2021

**Date Issued:** 19-12-2024  
**Revision nr:** 06