



# AUTOGEAR OIL EP

## 85W-140

### Product Description:

**AUTOGEAR OIL EP 85W-140** is an universal high performance mineral EP gear oil for use in manual transmission and transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-140 GL-4 is been required.

**AUTOGEAR OIL EP 85W-140** is formulated with high refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Good Extreme Pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR OIL EP 85W-140** exceeds the following performance criteria:

**API GL-4 MIL-L-2105**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	85W-140
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	902.8
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	376.5
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	27.3
Low-Temperature Brookfield Viscosity @ -12°	cP	ASTM D2983	52800
Viscosity Index		ASTM D2270	98
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-21

**Product Nr:** 43040

**Date Superseded:** 22-01-2021

**Date Issued:** 19-12-2024

**Revision nr:** 05