



AUTOGEAR OIL MP

75W-90

Product Description:

AUTOGEAR OIL MP 75W-90 is a universal high performance multi-purpose gear oil for use in differentials, axles and some transmissions of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 75W-90 GL-5 is been required.

AUTOGEAR OIL MP 75W-90 is based on a high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

AUTOGEAR OIL MP 75W-90 exceeds the following performance criteria:

API GL-5 **MIL-L-2105D** **MAN 342 M2** **Volvo STD 1273.1**
ZF TE-ML 05A, 7A, 16B, 17B, 21A



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	75W-90
Density@15°C	kg/m ³	ASTM D4052	869.0
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	97.6
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	15.0
Viscosity Index		ASTM D2270	162
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45

Product Nr: 43055
Date Superseded: 19-10-2022

Date Issued: 4-4-2025
Revision nr: 1