



# TO-4 TRANSMISSION FLUID 10W

## Product Description:

**TO-4 TRANSMISSION FLUID 10W** is specifically designed for powershift transmissions, final drives and wet brakes on heavy duty off-highway equipment used in earthmoving, mining logging, road transport and agricultural applications.

**TO-4 TRANSMISSION FLUID 10W** 10W is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals possible.

**TO-4 TRANSMISSION FLUID 10W** exceeds the following performance criteria:

Caterpillar TO-4	Caterpillar TO-2	Allison C-4	API GL-4
ZF TE-ML 03C	Vickers 35VQ25	Vickers I-286-S	Vickers M2950S
Komatsu Dresser	Komatsu KES 07.868.1	DANA Powershift transmissions	



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W
Density@15°C	kg/m³	ASTM D4052	860.5
Kin. Viscosity @40°C	mm²/s	ASTM D7042	37.0
Kin. Viscosity @100°C	mm²/s	ASTM D7042	6.4
Viscosity Index		ASTM D2270	126
Viscosity CCS @-25°C	cP	ASTM D5293	3230
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36

**Product Nr:** 43160  
**Date Superseded:** 24-6-2021

**Date Issued:** 30-12-2024  
**Revision nr:** 08