



ATF CVT FLUID

Product Description:

ATF CVT FLUID is a fully synthetic ultra-high performance CVT fluid formulated with selected base stocks and specially developed for use in the latest generation of Continuously Variable Transmission (CVT) – gearboxes which transfer traction via steel-made traction chain or push-belts.

ATF CVT FLUID is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Good thermo-and oxidation stability.
- Extended drain interval possible.
- Excellent anti-wear, anti-rust and anti-corrosion technology.
- High Viscosity Index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity assist in good cold start performance.
- Compatibility with all common seal materials

ATF CVT FLUID exceeds the following performance criteria:

Audi/VW G 052 180
Audi/VW G 052 516
BMW EZL 799A
FCA CVTF+4
GM DEX-CVT
GM CVT
Subaru e-CVTF
Subaru i-CVT F / FG
Toyota TC

Ford Mercon C
Ford M2C928-A
Honda HCF-2
Hyundai/Kia SP CVT-1
MB 236.20
Nissan NS-1/NS-2/NS-3
Subaru High Torque CVTF
Suzuki CVTF 3320
Toyota FE

Daihatsu Ammix CVTF-DC, CVTF-DFE
Ford WSS-M2C933-A
Honda Genuine CVT Fluid
Honda Multi Matic Fluid (HMMF)
Mazda CVTF 3320 / JWS 3320
Mitsubishi Dia Queen CVTF J1 / J4
Subaru Lineartronic CVTF / CVTF-II
Suzuki CVT Fluid Green 1 / 2
Toyota WS (JWS3324)



Property	Unit	Test Method	Typical Value
Color		Visual	Amber
Density @15°C	kg/m ³	ASTM D4052	848.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	34.3
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.0
Viscosity Index		ASTM D2270	174
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-51

Product Nr: 43250

Date Superseded: 03-10-2023

Date Issued: 4-4-2025

Revision nr: 06