



# SUPER TRACTOR OIL

## 10W-30

### Product Description:

**SUPER TRACTOR OIL 10W-30** is a high quality universal mineral based so called "Super Tractor Oil Universal" (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).



**SUPER TRACTOR OIL 10W-30** is formulated on high refined solvent mineral base stock in combination with an unique additive package to reach the following properties;

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

**SUPER TRACTOR OIL 10W-30** exceeds the following performance criteria:

<b>Engine Spec:</b>	API CG-4/CF-4/CE/SF	MB 227.1	ACEA E3
<b>STOU/UTTO Spec:</b>	JD J27, J20C	Ford M2C159B/C	MF M 1145
	FNH 82009201,2,3	Ford M2C86C	Ford M2C134A,C,D
	Case 1206,1209	MF M 1135/ 1139	MF M 1143/1144
	Caterpillar TO-2	API GL-4	Allison C-4
	CNH MAT 3525,3526	NH 030C	NH 024C
	NH 420A	NH 410B	ZF TE-ML 06A,B,C,R,07B
<b>Hydr. Spec:</b>	Eaton M-2950S	Eaton I-280-S	Danfoss

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-30
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	875.6
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	65.7
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	10.3
Viscosity Index		ASTM D2270	141
Viscosity CCS @-25°C	cP	ASTM D5293	6000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	10.7

**Product Nr:** 43270

**Date Superseded:** 16-12-2019

**Date Issued:** 3-1-2025

**Revision nr:** 03