

## INDUSTRIAL GEAR OIL

## **CLP 68**

## **Product Description:**

**INDUSTRIAL GEAR OIL CLP 68** is a high performance extreme pressure gear oils developed for lubrication of heavy duty industrial gears working under severe operating conditions.

**INDUSTRIAL GEAR OIL CLP 68** is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/ moisture.

INDUSTRIAL GEAR OIL CLP 68 exceeds the following performance criteria:

DIN 51517-3 CLP David Brown S1.53.101 AIST 224 (US Steel 224) ISO 12925-1 CKD AGMA 9005 E-02 AGMA 9005-F16 JIS K 2219:2006 class 2

Property	Unit	Test Method	Typical Value
ISO VG Grade		ISO 3448	68
Density@15°C	kg/m³	ASTM D4052	880.3
Kin. Viscosity @40°C	mm²/s	ASTM D7042	66.8
Kin. Viscosity @100°C	mm²/s	ASTM D7042	8.7
Viscosity Index		ASTM D2270	102
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27
FZG Fail Load Stage, min		DIN 51354-2	12
Total Acid Number	mg KOH/g	ASTM D664	<0.6

**Product Nr:** 43450 **Date Issued:** 7-1-2025

**Date Superseded:** 16-12-2019 **Revision nr:** 04

