## Product Data Sheet CHAIN SAW OIL 150

**Product Description:** 

CHAIN SAW OIL 150 is a high quality oil specially developed to lubricate the chain of chain saws.

CHAIN SAW OIL 150 is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Very good adhesive strength.
- Excellent lubricating properties, helps to prevent premature chain failure.
- Extend working life.
- The specially selected additives also inhibit rust.

## CHAIN SAW OIL 150 is NOT suitable to lubricate the engine.

Property	Unit	Test Method	Typical Value
ISO VG Class			150
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	888.6
Kin. Viscosity @40°C	mm²/s	ASTM D7042	154.9
Kin. Viscosity @100°C	mm²/s	ASTM D7042	15.4
Viscosity Index		ASTM D2270	101
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-15

**Product Nr:** 43880 **Date Superseded:** 20-12-2019 **Date Issued:** 9-1-2025 **Revision nr:** 02

77 B.V. | Van Ewijckskade 1C 1761 JA Anna Paulowna, The Netherlands | info@77lubricants.nl



## www.77lubricants.com