



MOTOR OIL VX

0W-30

Product Description:

MOTOR OIL VX 0W-30 is a high performance fuel saving LOW SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed.

MOTOR OIL VX 0W-30 is formulated with high quality synthetic base stocks (PolyAlphaOlefine) in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

MOTOR OIL VX 0W-30 exceeds the following performance criteria:

ACEA C3
BMW LL-04

VW 504 00 / 507 00

Porsche C30



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-30
Density@15°C	kg/m ³	ASTM D4052	843.3
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	64.1
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.3
Viscosity Index		ASTM D2270	193
Viscosity CCS @-35°C	cP	ASTM D2270	5800
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D7346	-53
Total Base Number	mgKOH/g	ASTM D2896	8.2
Sulphated Ash	%Wt	ASTM D874	0.7

Product Nr: 45290
Date Superseded: 04-03-2022

Date Issued: 4-4-2025
Revision nr: 04