

CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2204  
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5703. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC
Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or Accu-Drive gear drive #7890. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #2204*  
*Rev. 10/05*

*©2005 Edelbrock Corporation*  
*Brochure #63-0465*

CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2204  
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5703. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC
Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or Accu-Drive gear drive #7890. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #2204*  
*Rev. 10/05*

*©2005 Edelbrock Corporation*  
*Brochure #63-0465*

CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2204  
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5703. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC
Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or Accu-Drive gear drive #7890. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #2204*  
*Rev. 10/05*

*©2005 Edelbrock Corporation*  
*Brochure #63-0465*

CAMSHAFT: Performer RPM Roller Hydraulic  
CATALOG #2204  
ENGINE: Chevrolet 350-400 c.i.d. V8 (87-92)  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5703. Use stock ratio rocker arms only.

Duration at .004" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	44° ABDC
Exhaust	56° BBDC	2° ATDC
Centerlines:	Int: 107° ATDC	Exh: 117° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7800 or Accu-Drive gear drive #7890. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #2204*  
*Rev. 10/05*

*©2005 Edelbrock Corporation*  
*Brochure #63-0465*