



**CAMSHAFT: Performer RPM Hydraulic Roller  
PART #2210  
ENGINE: Chevrolet 350-400 c.i.d. V8 (55-86)  
RPM RANGE: 1500-6500**

**CAUTION:** Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	7° BTDC	47° ABDC
Exhaust	57° BBDC	1° ATDC
Centerlines:	Int 110° ATDC	Exh 118° BTDC
Lobe Separation:	114°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7800. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2210  
Rev. 7/09 - AJ/mc

©2009 Edelbrock Corporation  
Brochure #63-2210C



**CAMSHAFT: Performer RPM Hydraulic Roller  
PART #2210  
ENGINE: Chevrolet 350-400 c.i.d. V8 (55-86)  
RPM RANGE: 1500-6500**

**CAUTION:** Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	7° BTDC	47° ABDC
Exhaust	57° BBDC	1° ATDC
Centerlines:	Int 110° ATDC	Exh 118° BTDC
Lobe Separation:	114°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7800. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2210  
Rev. 7/09 - AJ/mc

©2009 Edelbrock Corporation  
Brochure #63-2210C



**CAMSHAFT: Performer RPM Hydraulic Roller  
PART #2210  
ENGINE: Chevrolet 350-400 c.i.d. V8 (55-86)  
RPM RANGE: 1500-6500**

**CAUTION:** Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	7° BTDC	47° ABDC
Exhaust	57° BBDC	1° ATDC
Centerlines:	Int 110° ATDC	Exh 118° BTDC
Lobe Separation:	114°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7800. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2210  
Rev. 7/09 - AJ/mc

©2009 Edelbrock Corporation  
Brochure #63-2210C



**CAMSHAFT: Performer RPM Hydraulic Roller  
PART #2210  
ENGINE: Chevrolet 350-400 c.i.d. V8 (55-86)  
RPM RANGE: 1500-6500**

**CAUTION:** Do not use dual valve springs. Use recommended or equivalent valve springs. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 296°	Exhaust 300°
Duration at .050" Lift:	Intake 234°	Exhaust 238°
Lift at cam:	Intake .359"	Exhaust .365"
Lift at valve:	Intake .539"	Exhaust .548"
Timing at .050 Lift:	Open	Close
Intake	7° BTDC	47° ABDC
Exhaust	57° BBDC	1° ATDC
Centerlines:	Int 110° ATDC	Exh 118° BTDC
Lobe Separation:	114°	

**CAUTION:** Use Edelbrock Performer-Link Timing Chain and Gear Set #7800. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2210  
Rev. 7/09 - AJ/mc

©2009 Edelbrock Corporation  
Brochure #63-2210C