

CAMSHAFT: Performer RPM Roller Hydraulic
PART #2261 & 2262
ENGINE: 1967 & Later Chevrolet 396-502
c.i.d. V8
RPM RANGE: 1500-6500



CAUTION: Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 335°	Exhaust 329°
Duration at .050" Lift:	Intake 236°	Exhaust 245°
Lift at cam:	Intake .368"	Exhaust .376"
Lift at valve:	Intake .625"	Exhaust .639"
Timing at .050 Lift:	Open	Close
Intake	6° BTDC	51° ABDC
Exhaust	54° BBDC	11° ATDC
Centerlines:	Int. 109° ATDC	Exh. 115° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2261, 2262
Rev. 5/16/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2261C

CAMSHAFT: Performer RPM Roller Hydraulic
PART #2261 & 2262
ENGINE: 1967 & Later Chevrolet 396-502
c.i.d. V8
RPM RANGE: 1500-6500



CAUTION: Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 335°	Exhaust 329°
Duration at .050" Lift:	Intake 236°	Exhaust 245°
Lift at cam:	Intake .368"	Exhaust .376"
Lift at valve:	Intake .625"	Exhaust .639"
Timing at .050 Lift:	Open	Close
Intake	6° BTDC	51° ABDC
Exhaust	54° BBDC	11° ATDC
Centerlines:	Int. 109° ATDC	Exh. 115° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2261, 2262
Rev. 5/16/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2261C

CAMSHAFT: Performer RPM Roller Hydraulic
PART #2261 & 2262
ENGINE: 1967 & Later Chevrolet 396-502
c.i.d. V8
RPM RANGE: 1500-6500



CAUTION: Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 335°	Exhaust 329°
Duration at .050" Lift:	Intake 236°	Exhaust 245°
Lift at cam:	Intake .368"	Exhaust .376"
Lift at valve:	Intake .625"	Exhaust .639"
Timing at .050 Lift:	Open	Close
Intake	6° BTDC	51° ABDC
Exhaust	54° BBDC	11° ATDC
Centerlines:	Int. 109° ATDC	Exh. 115° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2261, 2262
Rev. 5/16/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2261C

CAMSHAFT: Performer RPM Roller Hydraulic
PART #2261 & 2262
ENGINE: 1967 & Later Chevrolet 396-502
c.i.d. V8
RPM RANGE: 1500-6500



CAUTION: Use recommended valve springs with closed pressure of 175 lbs., open pressure of 465 lbs, and max lift of .700". Use stock ratio rockers only.

Duration at .004" Lift:	Intake 335°	Exhaust 329°
Duration at .050" Lift:	Intake 236°	Exhaust 245°
Lift at cam:	Intake .368"	Exhaust .376"
Lift at valve:	Intake .625"	Exhaust .639"
Timing at .050 Lift:	Open	Close
Intake	6° BTDC	51° ABDC
Exhaust	54° BBDC	11° ATDC
Centerlines:	Int. 109° ATDC	Exh. 115° BTDC
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

Part #2261, 2262
Rev. 5/16/13 - QT/mc

©2013 Edelbrock LLC
Brochure #63-2261C