

Purolator Filter Guide



[PurolatorBOSS™](#)



[PurolatorONE™](#)



[Purolator](#)

Oil Change Interval*	Up to 15,000 miles*	Up to 10,000 miles*	Up to 5,000 miles
Suggested Oil Type**	Full synthetics and extended performance**	High mileage & synthetics**	Conventional & high mileage**
Vehicle Coverage	Popular vehicles	Most popular vehicles - import and domestic	Nearly all vehicles on the road
Driving Habits	Extreme stop-and-go; city driving, frequent towing/hauling	City driving, stop-and-go; towing/hauling	Typical/highway driving
Driving Environment	Extreme temperatures, mountains, demanding city traffic	City traffic, dusty roads	Everyday - city and highway
Dirt Removal Power	99% +	99%	96.5%
Dirt Removal Capacity	27g	15g	13g
Media Material	100%, full-synthetic SmartFUSION Technology™ media	High-density synthetic blend media	Multi-fiber, high density media
Anti-Drainback Valve	Silicone - performs better longer	Silicone - performs better, longer	Nitrile
Gasket	Ethylene-acrylic PuroSEAL Gasket™	Silicone	Nitrile
End Caps	Metal	Metal	Metal
Center Tube	Double-helix metal	Double-helix metal	Double-helix metal