

Overview

PN 558-128 is a device that allows for an ECU input to be safely connected directly to the +12V side of the transbrake solenoid. This device protects the ECU input from damaging flyback voltage which occurs when the transbrake is released.

Installation

- 1. There are three wires that need to be connected as follows:
 - **Red** Connect to the +12V side of the transbrake that is powered when the transbrake is activated.
 - **Blue** Connect to the ECU input. This will be an "H" type input in the Holley ECU. This will come with an ECU pin pre-crimped.
 - **Black** Connect to a vehicle chassis ground.

Holley® Performance Products 1-270-781-9741 or 1-866-464-6553 www.holley.com

© 2015 Holley Performance Products, Inc. All rights reserved.

199R10871 Date: 7-28-15



Overview

PN 558-128 is a device that allows for an ECU input to be safely connected directly to the +12V side of the transbrake solenoid. This device protects the ECU input from damaging flyback voltage which occurs when the transbrake is released.

Installation

- 1. There are three wires that need to be connected as follows:
 - Red Connect to the +12V side of the transbrake that is powered when the transbrake is activated.
 - **Blue** Connect to the ECU input. This will be an "H" type input in the Holley ECU. This will come with an ECU pin pre-crimped.
 - **Black** Connect to a vehicle chassis ground.

Holley® Performance Products 1-270-781-9741 or 1-866-464-6553 www.holley.com

© 2015 Holley Performance Products, Inc. All rights reserved.

199R10871 Date: 7-28-15