

**NOW
AVAILABLE!**



ANNOUNCES

CLASS 1 HIGH PERFORMANCE FORCED INDUCTION CAMSHAFT FOR CHRYSLER 5.7L, 6.2L & 6.4L HEMI ENGINES

CHRYSLER	5.7-T (345)	OHV	2009-23	300	JEEP	5.7-T (345)	OHV	2009-10	Commander
CHRYSLER	5.7-T (345)	OHV	2009	Aspen	JEEP	5.7-T (345)	OHV	2009-23	Grand Cherokee
CHRYSLER	6.4-J (392)	OHV	2012-14	300	JEEP	5.7-T (345)	OHV	2021-24	Grand Cherokee L
CHRYSLER	6.4-J (392)	OHV	2023	300	JEEP	5.7-T (345)	OHV	2022-23	Wagoneer
DODGE	5.7-T (345)	OHV	2009-23	Challenger	JEEP	6.2-9 (376)	OHV	2018-21	Grand Cherokee
DODGE	5.7-T (345)	OHV	2009-23	Charger	JEEP	6.4-J (392)	OHV	2012-23	Grand Cherokee
DODGE	5.7-T (345)	OHV	2009-25	Durango	JEEP	6.4-J (392)	OHV	2021-26	Wrangler
DODGE	5.7-T (345)	OHV	2009-10	Ram1500	RAM	5.7-T (345)	OHV	2011-24	1500
DODGE	5.7-T (345)	OHV	2009-10	Ram 2500	RAM	5.7-T (345)	OHV	2011-18	2500
DODGE	5.7-T (345)	OHV	2009	Ram 3500	RAM	5.7-2 (345)	OHV	2012-18	2500
DODGE	6.2-9 (376)	OHV	2015-23	Challenger	RAM	5.7-T (345)	OHV	2011-18	3500
DODGE	6.2-9 (376)	OHV	2015-23	Charger	RAM	6.2-9 (376)	OHV	2021-24	1500
DODGE	6.2-9 (376)	OHV	2021-26	Durango	RAM	6.4-J (392)	OHV	2014-26	2500
DODGE	6.4-J (392)	OHV	2011-23	Challenger	RAM	6.4-J (392)	OHV	2014-26	3500
DODGE	6.4-J (392)	OHV	2012-23	Charger	RAM	6.4-J (392)	OHV	2014-24	4500
DODGE	6.4-J (392)	OHV	2018-24	Durango	RAM	6.4-J (392)	OHV	2014-24	5500

**Part number
23109
UPC: 729295524366**



CLASS 1 HYDRAULIC ROLLER BOOST CAMSHAFT

- RPM Range: 3400-7000
- Forced Induction/Boost Camshaft
- Requires MDS Delete, VVT Lockout and Aftermarket Valve Springs
- 115° Lobe Separation
- 0.620" Intake Valve Lift
- 0.620" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 222°
- Exhaust Duration @ .050 Inch Lift 230°

Good idle quality. Low RPM torque and mid range performance. Will work with stock or slightly modified engine. Manual or auto transmission.

**** Always consult catalog listings for detailed application information ****

Melling Engine Parts

P.O. Box 1188 • Jackson, MI 49204 • www.melling.com